

ICA-3plus 12/24/48V-1500~6000W

The Ultimate Interactive DC to AC Pure Sine Wave Inverter/Charger Power Management Control System Ideally Designed for Home, Boat, Caravan or RV



Features

- Combi-functional, with intelligent shore and generator power management
- Uninterrupted AC power (UPS function)
- Virtually unlimited power thanks to parallel operation
- Three phase capability
- **PowerControl** – Dealing with limited generator, shore side or grid power to avoid sudden loads on generator causing voltage spikes
- **PowerSupport** – Boosting the capacity of shore or generator power, an innovative feature of the ICA-3 plus
- Four stage adaptive charger and dual battery charging
- LCD display for parameter setting and error messages
- Programming auxiliary relay (X 3)
- Programming input current limit for power share
- Communication with max. 10 sets of solar chargers (HeliStar Series)
- Four preset control mode application with AC grid, AC charging and solar charging
- Wall Mount and Table Mount available for choices
- Optional remote panel with LCD display for easy operation in distance

ICA-3plus 12/24/48V-1500~6000W

Specifications

12 Volt System	ICA-3 plus-1500-12X(1)	ICA-3 plus-3000-12X(1)
MODEL 24 Volt System	ICA-3 plus-1500-24X	ICA-3 plus-3000-24X
48 Volt System	ICA-3 plus-1500-48X	ICA-3 plus-3000-48X
GENERAL		
Ventilation	Forced cooling	Forced cooling
Temperature – Operation	-20°C ~ +70°C	-20°C ~ +70°C
– Storage	-25°C ~ +80°C	-25°C ~ +80°C
Protection	Output short circuit, Over load, Battery overvoltage, Battery undervoltage, Battery reverse polarity detection, Over temp., High input voltage ripple	
Humidity	0~95% (non condensing)	0~95% (non condensing)
Power control Function	✓	✓
Power assist Function	✓	✓
Uninterrupted AC power	✓ (Less than 10 msec)	✓ (Less than 10 msec)
Adaptive 4-stage charge	✓	✓
Two output to charge 2 battery banks	✓	✓
Auxiliary Relay	X 3	X 3
Parallel operation	✓ (Max. 5 sets)	✓ (Max. 5 sets)
3-phase capacity	✓	✓
Battery voltage sensor	✓	✓
INVERTER		
Input Voltage Range (VDC)	9.5 -16V / 19-32V / 38-64V	
Output Voltage (VAC)	185 ~ 240 VAC / 90~120 VAC	
Output Frequency	50Hz / 60Hz ± 0.1%	
Output Waveform	Pure sinewave	
Output Voltage THD	< 5%	
Power Factor (All Loads)	✓	
No linger load, crest factor	3: 1	
Cont. Power Output (W) Under 70°C (cos θ=1.0)	1500W (No derate)	3000W (No derate)
Cont. Power Output (W) Over 70°C (cos θ=1.0)	0W (Shutdown)	0W (Shutdown)
Maximum Power (W)	3000W	6000W
Maximum Efficiency (%)	82/84/85	84/86/89
Zero-load Power (W)	8W	12W

CHARGER		
Input Voltage Range (VAC)	200~250 VAC / 100~125 VAC	
Input Frequency	45 - 55 Hz / 55 - 65 Hz	
Power Factor	1	
Charge Characteristic	4-stage adaptive / Bulk-Absorption-Float-Equalize	
Maximum DC Voltage Ripple (Vrms)	< 1.25 V	
Charge Current House Battery (A)	70A/40A/20A	140A/70A/40A
Charge Current Starter Battery (A)	4A	
Absorption Voltage Default (VDC)	14.4V / 28.8V / 57.6V	
Float voltage Default (VDC)	13.8V / 27.6V / 55.2V	
Equalize Voltage default (VDC)	13.2V / 26.4V / 52.8V	
Output Charge Voltage (min ~ max)	8V~16V / 11V~32V / 22V~64V	
Battery Temperature sensor	BTS-3	
AC INPUT SWITCH		
AC IN Terminal Circuit Breaker	30A (110V) / 15A (220V)	60A (110V) / 30A (220V)
Switch-over Time		
a. inverter to AC input	0 msec	
b. AC input to inverter	0 msec	
Detection Time AC Input Fault	4 ~ 10 msec	
Trip Level AC Input to Inverter	90 VAC / 180 VAC	
Trip Level Inverter to AC Input	94 VAC / 187 VAC	
Min.~ Max. Frequency Range	45-55 Hz / 55-65 Hz	
MECHANICAL		
Cabinet / Protecting Class	Aluminum / IP20	
Dimension (HxWxD)	362 x 258 x 370 mm	424 x 258 x 370 mm
Weight (kgs)	16 kgs	35 kgs
OPTIONS		
Solar Charger	HeliStar Series J-45A/J-60A (Max. 10 sets for parallel connection)	
Remote Controller	Remote monitoring available, optional cables: 3M/15M	
Battery Temperature Sensor (BTS-3)	Compensation for the battery charging voltage and current	

(1) X should be 1, output voltage = 90~120 VAC or 2, output voltage = 185~240 VAC